



RAE Products & Chemicals Corporation

# 2721 CLEAR URETHANE SEALER FLOOR COATING & SEALING

High VOC - Solvent-Base

Product Description	Product Characteristics
<p>This solvent based, Oil-Modified Urethane is a durable sealer formulated to protect concrete, wood, tile, and other flooring surfaces. Can also be used a protective top-coat over other paint coatings.</p>	<p>Vehicle Type: Urethane</p> <p>Viscosity: 17 - 21 cps</p> <p>Gloss: Full</p>
Application Procedures	
<p>Stir all containers thoroughly before using. Paint only in dry weather. Straining the paint when using spray equipment is recommended. May be applied by a marking machine, roller or brush. No priming is required. Apply to a wet film thickness of 5 to 10 mils. When painting in cold temperatures, the warmer the paint the easier it is to spray.</p>	<p>Weight Solids: 38.02% ± 1.00%</p> <p>Volume Solids: 31.06% ± 1.00%</p> <p>Density (Weight per Gallon): 7.31 ± 0.20 lbs/gal</p> <p>VOC: 4.44 lb/gal</p>
Handling Safety	
<p>DO NOT SMOKE WHILE USING THIS PRODUCT. Keep away from open flame. Avoid prolonged or repeated contact with skin. Avoid breathing of vapors or spray mist. Do not take internally. Close container after each use. Wear respirator, eye protection and protective clothing when handling. See MSDS for further information.</p>	<p>VOC: 532 g/L</p> <p>Reducer: Mineral Spirits</p> <p>Dry Film Thickness: Minimum 1.0 mils dry</p> <p>Cure Schedule: 3 hours (air dry)</p> <p>(Note: Applied film thickness, relative humidity, and temperature will effect dry time)</p>
Preparation	
<p>The surface to be painted must be dry, free of grease and oil and brushed free of loose dirt. Striping paints will not adhere to unclean surfaces. Application equipment must be clean from all previous paint(s).</p> <div data-bbox="110 1455 488 1623"> <p><b>PERSONAL PROTECTIVE EQUIPMENT</b></p> <p>Splash Goggles + Gloves + Synthetic Apron + Dust and Vapor Respirator</p> </div> <div data-bbox="505 1465 792 1604"> </div>	<p>Shelf Life: 12 months if unopened and stored in a cool area.</p> <p><i>Note: These results in Performance &amp; Product Characteristics represent actual control values when tested under laboratory conditions. To the best of our knowledge, the above technical data is true and accurate at the date of issuance but is subject to change without prior notice.</i></p>

The following supersedes any provision contained in the forms, letters and papers of your company. This product is designed and intended for professional application only. All products should be thoroughly tested under application conditions prior to use. The information contained herein is believed to be reliable. **HOWEVER, RAE PRODUCTS & CHEMICALS CORPORATION MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** UNDER NO CIRCUMSTANCES SHALL RAE PRODUCTS & CHEMICALS CORP. BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OF WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF RAE PRODUCTS & CHEMICALS CORP. FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY RAE PRODUCTS & CHEMICALS CORP. SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER.

**CAUTION: DANGER! FLAMMABLE! VAPORS MAY CAUSE FLASH FIRE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. INJURIOUS TO EYES. KEEP OUT OF THE REACH OF CHILDREN!** BEFORE using this product it is essential that the "Material Safety Data Sheet" describing the product as well as the "Product Label" be reviewed. If your company does not have such information or has any questions, contact **RAE Products at 1-708-396-1984 or refer to data at [www.raepaint.com](http://www.raepaint.com)**