




5350 CLEAR ACRYLIC SEALER FLOOR COATING & SEALING

For use over painted line stripes

Product Description	Product Characteristics
<p>Clear acrylic waterborne sealer designed to prolong the life of traffic and zone marking coatings. When applied over aisle markings on surfaces of shop and warehouse areas this product will help minimize dirt pick up and extend the durability of the markings.</p>	<p>Vehicle Type: Acrylic</p> <p>Viscosity: 22 - 25" #3 EZ Zahn</p> <p>Gloss: Semi</p>
Application Procedures	<p>Weight Solids: 32.00% ± 1.00%</p> <p>Volume Solids: 28.00% ± 1.00%</p> <p>Density (Weight per Gallon): 8.72 ± 0.20 lbs/gal</p> <p>VOC (minus exempts): 161 g/L</p> <p>VOC (with exempts): 60 g/L</p>
<p>The surface to be coated must be clean, dry, and free from any contaminants such as oil or grease. Application equipment must be clean from all other coatings before use. The markings to be sealed shall be allowed to cure for a minimum of 24 hours before sealing. This product is supplied ready to use and does not normally require thinning. If necessary, water can be used as a reducer.</p>	<p>Application: Spray, brush, or roll</p> <p>Dry Film Thickness: Minimum 3-5 mils dry</p> <p>Cure Schedule: 30 min (air dry)</p> <p><i>(Note: Applied film thickness, relative humidity, and temperature will effect dry time - wait 24 hours before opening up to heavy traffic)</i></p> <p>Shelf Life: 12 months if unopened and stored in a cool area.</p>
Handling Safety	
<p>DO NOT SMOKE WHILE USING THESE PRODUCTS. These products contain flammable solvents. Keep away from open flame. Close and seal container after each use. Empty containers may still contain flammable vapors and should be treated the same as full containers. Avoid prolonged or repeated contact with skin. Avoid breathing of vapors or spray mist. Do not take internally. Wear respirator, eye protection and protective clothing when handling. Store in a cool dry place, do not store outdoors or in direct sunlight. See MSDS for further information.</p>	
Safety Warnings	
  	<p><i>Note: These results in Performance & Product Characteristics represent actual control values when tested under laboratory conditions. To the best of our knowledge, the above technical data is true and accurate at the date of issuance but is subject to change without prior notice.</i></p>
<p>The following supersedes any provision contained in the forms, letters and papers of your company. This product is designed and intended for professional application only. All products should be thoroughly tested under application conditions prior to use. The information contained herein is believed to be reliable. HOWEVER, RAE PRODUCTS & CHEMICALS CORPORATION MAKES NO WARRANTY CONCERNING THIS PRODUCT, WHETHER EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL RAE PRODUCTS & CHEMICALS CORP. BE LIABLE FOR SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR ANY OTHER DAMAGES FROM ALLEGED NEGLIGENCE, BREACH OF WARRANTY, STRICT LIABILITY, OR ANY OTHER LEGAL THEORY, ARISING OUT OF THE USE OR HANDLING OF THIS PRODUCT. THE SOLE REMEDY OF THE BUYER AND THE SOLE LIABILITY OF RAE PRODUCTS & CHEMICALS CORP. FOR ANY CLAIMS SHALL BE LIMITED TO THE BUYER'S PURCHASE PRICE OF THE PRODUCT WHICH IS THE SUBJECT OF THE CLAIM OR THE AMOUNT ACTUALLY PAID FOR SUCH PRODUCT, WHICHEVER IS LESS. TECHNICAL ADVICE FURNISHED BY RAE PRODUCTS & CHEMICALS CORP. SHALL NOT CONSTITUTE AN EXPRESS WARRANTY, WHICH IS EXPRESSLY DISCLAIMED. ALL TECHNICAL ADVICE GIVEN IS ACCEPTED AT THE RISK OF THE BUYER.</p> <p>CAUTION: DANGER! FLAMMABLE! VAPORS MAY CAUSE FLASH FIRE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. INJURIOUS TO EYES. KEEP OUT OF THE REACH OF CHILDREN! BEFORE using this product it is essential that the "Material Safety Data Sheet" describing the product as well as the "Product Label" be reviewed. If your company does not have such information or has any questions, contact RAE Products at 1-708-396-1984 or refer to data at www.raepaint.com</p>	